

Product code:GL149

RHINOweld, Cat III “Hi- Deposition” aluminised back welding gauntlet



Branding:

**GL149**  
size 10

**CE 0362**

EN388



3 2 2 3

EN12477A  
EN407



3 1 3 4 3 x

Technical data:

RHINOweld high deposition, A370 aluminised back welding gauntlet. Double layer 170gsm Para Aramid felt liner to back of glove from finger tips to wrist. 1.3mm green side split leather palm, natural colour cuff, fully welted, wing thumb. 100 deg C contact heat to palm, 1000 deg C radiant heat to back. Kevlar stitching and 100% cotton bleached lining to cuff, rest of glove fully lined with 100% bleached brushed cotton. High abrasion resistance. Sized larger to compensate for extensive protective inner layers. Specifically designed to offer superior levels of radiant heat protection to the back of the hand.

Cat III EN388: Abrasion - 3, Cut - 2, Tear - 2, Puncture - 3

(glove test scores based on 1 = lowest, 5 = highest)

EN12477 Type A & EN407 : Burning behaviour - 3, Contact heat - 1, Convective heat - 3, Radiant heat - 4, Small splashes molten metal - 3, Large splashes molten metal - x  
(glove test scores based on 1 = lowest, 5 = highest)

Packaging

6 pairs packed in a plain polybag + 1 English language User Guide per bundle, 10 bundles to an export carton. Carton with product code and carton quantity on both ends.

For more detailed packing instructions, please refer to packaging specification PKGS 004